





The **CleanStation SRS 2P-H** is a low-cost, full-feature support removal system optimized to accommodate large FDM parts.

This professional-grade system offers a variable flow option, which allows the operator to control jet flow rates for delicate parts. The SRS 2P-H has appliance style "quick disconnect" plumbing and it can also be hard wired and plumbed into place. The CleanStation patented "Heat, Agitation, and Flow" technology is not load sensitive. Unlike ultrasonic cleaning tanks, all CleanStation systems are capable of efficient "batch processing."

For use with: F270, F370, Fortus 360mc/380mc/400mc/450mc

Product Features

- Most efficient recirculation for support removal
- Large capacity, high performance
- Variable speed control
- "Single touch" automated control
- Programmable for time and temperature
- High-efficiency, multi-point manifold
- Recessed "no drip" top
- Interior parts basket with hinged, locking lid

Product Specifications

- Work envelope: 18.25" x 14.125" x 16"
- Machine dimensions: 36" x 30" x 40"
- Power requirements: Single phase 220v, 20 amp service
- ◆ Capacity: 4,132 cubic inch, 19.5 gallon
- Shipping weight 430 lbs

For additional product information, email sales@cleanstation-srs.com or call 763-425-1383 x 309

CleanStation-SRS.com

- Basket self-drains into tank
- Quick-disconnect, appliance style plumbing
- ◆ Stainless steel tank
- Chemical resistant
- Patented "Heat, agitation and flow" technology
- ◆ 1 year warranty
- ◆ Made in USA



