

# CleanStation® SRS II™

"First Choice of FDM Professionals"



**Supports the Fortus 360MC  
and 400MC**

*CleanStation patented "Heat, Agitation, and Flow" technology is not load sensitive. Unlike ultrasonic cleaning tanks, all CleanStation systems are capable of efficient "batch processing."*

*The CleanStation SRS II is a heavy duty, "professional grade" support removal optimized to accommodate large FDM parts and quantities of DDM parts.*

*To protect delicate parts, the system is equipped with active cooling to prevent warping and de-lamination due to overheating. The SRS II is also available with a variable flow option which allows operators to control jet flow rates.*

*The SRS II is mobile and self contained. It is mounted on lockable casters and equipped with appliance style "quick disconnect" plumbing. It may be hard wired and plumbed into place or rolled from one space to another.*

## Product Specifications

- \* large capacity high performance CleanStation®
- \* 16"x 14"x 16" work envelope
- \* 3584 cubic inch, 17 gallon, stainless steel tank
- \* integrated rinse sink and faucet
- \* "single touch" automated control
- \* programmable for time and temperature
- \* 3000 watt heater
- \* 1 hour warm up
- \* circulation: 167% per minute
- \* quick disconnect, appliance style plumbing
- \* single phase 240v, 20 amp service
- \* rolls on locking casters
- \* high efficiency single point manifold
- \* hinged and locking tank lid, hinged basket lid
- \* Recessed "no drip" top
- \* 1 year warranty
- \* Shipping weight 430lbs

**Product Info: 763-425-1383 x102 or SGreen@PM3Tech.com**



# CleanStation-SRS.com

PM Technologies  
PO Box 493  
Osseo, MN 55369